NSN 5935-01-141-2652

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-141-2652

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.203 inches

Overall Height:

0.660 inches

Overall Width:

0.336 inches

Unthreaded Mounting Hole Diameter:

0.116 inches

Distance Between Mounting Facility Centers:

2.938 inches

Board Accommodated Length:

2.504 inches single board

Board Accommodated Width:

0.054 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

550.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 cl 4 military specification 2nd treatment response single mating end single contact grouping and qq-n-290 cl 2 federal specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Wire loop single mating end single contact grouping

Insert Material Specification:

Mil-n-10833 military enecification single material response single mating and

NSN 5935-01-141-2652

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 15 single mating end single contact grouping Included Contact Type: Bifurcated spring single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.015 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.