NSN 5935-01-141-4195

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-141-4195

| View Online at https://aerobasegroup.com/nsn/5935-01-141-4195 |
|--------------------------------------------------------------------------------------------------------------------|
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.743 inches |
| Overall Diameter: |
| 1.471 inches |
| Environmental Protection: |
| Moisture proof and salt water resistant and shock proof and vibration proof |
| Mating End Quantity: |
| 2 |
| Contact Position Arrangement Style: |
| 23-2 all mating ends |
| Contact Removability: |
| Nonremovable all mating ends single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 80.0 and 142.0 and 196.0 and 293.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Contact Material: |
| Copper alloy all mating ends single contact grouping |
| Contact Surface Treatment: |
| Gold all mating ends single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, cl 2 military specification single treatment response all mating ends single contact grouping |
| Shell Material: |
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Chromium |
| Shell Material Specification: |
| Qq-a-367, t6 federal specification single material response |
| Included Contact Quantity: |
| 85 all mating ends single contact grouping |
| Included Contact Type: |
| Round socket all mating ends single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |

0.170 gold grains, troy

Precious Material And Weight:

NSN 5935-01-141-4195

Connector Adapter - Page 2 of 2



| Precious Material: |
|--------------------------------|
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-g-45204 spec.