NSN 5935-01-141-9408

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-141-9408 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.707 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Environmental Protection:** Vibration resistant and shock resistant and corrosion resistant and moisture resistant and thermal shock resistant **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.340 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Distance From Mounting Shoulder To Front Face:** 0.442 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Osm single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-141-9408

Electrical Receptacle Connector - Page 2 of 2



| Contact Surface Treatment: |
|---|
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polytetrafluoroethylene single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Steel |
| Shell Material Specification: |
| Qq-s-764, cl 303 federal specification single material response |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Included Contact Type: |
| Coaxial pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Ū

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.