NSN 5935-01-142-1042

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-142-1042

Thread Class: 2a and 2b **Thread Direction:** Left-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 1.565 inches and 1.655 inches **Overall Diameter:** 1.264 inches **Environmental Protection:** Explosion proof and moisture resistant and shock resistant and vibration resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 16-9 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 23.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring **Thread Length:** 0.598 inches Thready Qty Per Inch (tpi): 20 and 5 **Thread Size:**

Terminal Location:

0.875 inches and 1.000 inches

Back single mating end all contact groupings

NSN 5935-01-142-1042Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
500 hr salt spray test for qualification per mil-std-1344 and mil-c-38999
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unef and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0