Electrical Connector Backshell - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-142-7299

Tread Dise: Teread Direction: Toread Direction:		
Tread Direction: Right-hand Sel Matrial: Right-hand Right-hand Right-hand Right-hand Right-hand Right-hand Right-hand Right-hand Soural Height: 2.011 Inches Overall Height: 2.021 Inches Oberland Diameter: Between 0.750 Inches and 1.250 Inches Cable Opening Quantity: Performed packing Seal Type: Proformed packing Solar Opening Quantity: Proformed packing Solar Opening Chantity: 1 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.375 Inches Maerial: Auriant alloy Surface Treatment: Nickel Stript Developation: Stript Developation: Nickel Thread Series Designator: Nickel Thread Series Designator: Nickel Stript Thread Series Desig	Thread Class:	
Right-hand Sead Material: Rubber, neoprene latex Overall Meight: 301 Inches Overall Width: 1.552 Inches Outerall Depining Diameter: Between 0.750 inches and 1.250 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 20 Nourning Facility Type And Quantity: 1 1 Thread Coupling Thread Coupling 1 Material: 1.375 Inches Stride Treatment: Nickel Stride Stride Designator: Nickel Thread Stride Designator: Nickel Nickel Thread Stride Designator: Nickel Nickel Thread Stride Designator: Nickel Thread Stride Designator: Nickel Thread Stride Designator: Nickel Stride Treatment: Nickel Thread Stride Designator: Nickel Stride		
Seal Material: Rubber, neoprene latex Overall Height: 2.031 Inches Overall Vidtht: 1.562 Inches Cable Opening Diameter: Between 0.750 Inches and 1.250 Inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Dessignation: 20 Mounting Facility Type And Quantity: 1 Threaded coupling Threaded coupling Threaded coupling Murationg Facility Type And Quantity: 1 formead packing Threaded coupling Threaded coupling Murationg Nation 1/2 1/3 State Seal Type: 1/3 1/3 State Seal Type 1/4 Muration Sufface Textment: Nickel State Seal Textment: Nickel Thread Seals Designator: Nickel State Seals Designator: Nickel State Seals Designator:		
Rubber, neoprene latex Overall Height: 2.031 incles Overall Width: 1.562 incles Cable Opening Diameter: Between 0.750 inches and 1.260 inches Cable Opening Quantity: 1 Seal Tope: Preformed packing State Designation: 20 Mounding Facility Type And Quantity: 1 threaded coupling Thready Qty Par Inch (tpl): 18 Thread Size: 1.375 inches Matorial: Atuminum alloy Stright pay websel elamp Stright per websel elamp Stright per websel elamp Stright Per selection Nickel Thread Stright Cartement: Nickel Stright Per websel elamp Stright Per webselle elamp Nickel Thread Stright Per webselle elamp Nickel Thread Stright Per webselle elamp Nickel Stright Per webselle elamp Stright Per webselle elamp Nickel Thread Stright Per websele		
Overall Height:2.031 inches2.041 inchesOverall Width:1.552 inchesCable Opening Diametor:Between 0.750 inches and 1.250 inchesCable Opening Quantity:1Sall Type:Preformed packingSize Designation:20Mounting Facility Type And Quantity:1 threaded couplingThreaded couplingThreaded couplingThreaded Size:1.375 inchesMaterial:Aurinum alloySurface Treatment:NickelSite Designator:Chread Size:Straight type weable clampGuardace Treatment:NickelStraight type weable clampChread StraigSite Treatment:NickelStraight type weable clampStraight type weable clampChread Straight type weable clampSite Treatment:NickelStraight type weable clampSite Treatment:NickelStraight type weable clampSite Treatment:NickelSite Treatment:Nickel <th></th> <th></th>		
2031 inches 2041 With: 1.552 inches 2152 inches 226 Opening Uamete: 226 Opening Uamete: 227 238 249 249 240 24 24 24 24 24 24 24 24 24 25 25 25 25 25 25 25 25 25 25 25 25 25		
Neveral Width:1.562 inches2 belveen 0.750 inches and 1.250 inches2 belveen 0.750 inches and 1.250 inches2 belveen 0.750 inches and 1.250 inches2 bel Type:9 reformed packing2 belsenation:208 belsenation:209 belsenation:209 belsenation:211 threaded coupling1 belsenation:229 belsenation:239 belsenation:249 belsenation:259 belsenation:269 belsenation:279 belsenation:289 belsenation:29 belsenation:29 belsenation:20 belsenation:20 belsenation:21 belsenation:22 belsenation:23 belsenation:24 belsenation:25 belsenation:25 belsenation:26 belsenation:27 belsenation:28 belsenation:29 belsenation:20 belsenation:20 belsenation:21 belsenation:22 belsenation:23 belsenation:24 belsenation:25 belsenation:26 belsenation:27 belsenation:28 belsenation:29 belsenation:29 belsenation:20 belsenation:20 belsenation:20 belsenation:21 belsenation:22 belsenation:23 belsenation:24 belsenation:25		
1.662 inches Cable Opening Quantity: 2 Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 Threaded coupling Threaded coupling Threaded Coupling Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Threaded Xty Per Inch (tpl): 18 Size Designator: 1.375 inches Matrial: Aluminum alloy Surface Treatment: Nickel Stright type wickable clamp Surface Treatment: Nickel Stright type wickable clamp Surface Treatment: Nickel Stright type wickable clamp Surface Treatment: Nickel Thread Stries Designator: Unif Stright type wickable clamp Stright type wickable clamp Nickel T	2.031 inches	
Cable Opening Quantity: Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Threaded Size: 1.375 inches Material: Aluminum alloy Stride Size Size Treatment: Nickel Stride Size Treatment: Nickel Strid Size Treatment:		
Between 0.750 inches and 1.250 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpt): 18 Thread Size: 1.375 inches Material: Aluminum alloy Style Designator: Style Designator: Straight type wicable clamp Stratest Designator: Nickel Thread Straige: Nickel Thread Straige: Nickel Style Designator: Nickel Thread Straige: Nickel Thread Straige: Nickel Thread Straige: Nickel Thread Straige: Nickel Straige: Nickel Thread Straige: Nickel Straige: Nickel Straige: Straige: Straige: Nickel Straige: Straige: </th <th>1.562 inches</th> <th></th>	1.562 inches	
Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Pe Ind (tpi): 18 Thread Size: 1.375 inches Material: Auminum alloy Surface Treatment: Nickel Strajent type wicable clamp Strajent type wicable clamp Nickel Thread Series Designator: Nickel Suff Thread Series Designator: <th>Cable Opening Diameter:</th> <th></th>	Cable Opening Diameter:	
1 Seal Type: Preformed packing Size Designation: 32 Mounting Facility Type And Quantity: 1 threaded coupling Material: Aduminum alloy Surface Treatment: Nickel Straight type wickable clamp Surface Treatment: Nickel Thread Series Designator: Unif Straight type wickable clamp Straight type wickable clamp It of the sure: Nickel Thread Series Designator: Unif Nickel It of the sure: <	Between 0.750 inches and 1.250 inches	
Seal Type: Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.375 inches Aluminum alloy Surface Treatment: Nickel Stright type wickable clamp Stright type wickable clamp Stright type wickable clamp Interd Stright type wickable clamp Materiat: Nickel Thread Stright type wickable clamp Stright type wickable clamp Interd Stright type wickable clamp Stright type wickable clamp Interd	Cable Opening Quantity:	
Preformed packing Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded coupling Threaded size: 1.375 inches Material: 1.375	1	
Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.375 inches Material: Aluminum alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Ounfd Sheff Life: Nickel Sheff Life: Nick Dund Sheff Life: Nick Fine Component: Nick Fine Component: Nick Sheff Life: Nick Fine Component: Nick Sheff Life: Nick Sheff Life: Nick Sheff Life: Nick Sheff Life: Sheff Life: Sheff Life: Sheff Life: Sheff Life: Sheff Life:	Seal Type:	
20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 13 Thread Size: 1.375 inches Material: 1.375 inches Material: 1.375 inches Material: 1.375 inches Material: Auminum alloy Surface Treatment: Nickel Surface Treatment: Nickel Surface Treatment: Nickel Thread Series Designator: Unef Sheff Life: Na Sheff Life: Na Suff Measure: T- Demilitarization: No	Preformed packing	
Mounting Facility Type And Quantity: 1 threaded coupling Thready Quy Per Inch (tpi): 18 Thread Size: 1.375 inches Material: Auminum alloy Surface Treatment: Nickel Stright type w/cable clamp Stright type w/cable clamp Nickel Thread Series Designator: Unef Sheff Life: Na Dird Measure: Na Dird Measure: Na Fig:	Size Designation:	
1 threade coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.375 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Stright type w/cable clamp Stright type w/cable clamp Mickel Thread Series Designator: Unof Sheff Life: N/a Unof Sheff Life: N/a Li	20	
Thready Qty Per Inch (tpi):18Thread Size:1.375 inchesMaterial:Aluminum alloySurface Treatment:NickelStyle Designator:Striaght type w/cable clampSurface Treatment:NickelDurface Treatment:NickelDurface Treatment:UnefShelf Life:NickDurfSurface Treatment:NickelDurfShelf Life:NickDurf for Surger:NickDurf for Surger:NickJit Of Measure:NaDurf for Surger: <t< th=""><th>Mounting Facility Type And Quantity:</th><th></th></t<>	Mounting Facility Type And Quantity:	
18 Thread Size: 1.375 inches Material: Naterial: Aluminum alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Enelliterication: Na Toread Series Designator: Inaf Shelf Life: N/a Enelliterication: Na Fig:	1 threaded coupling	
Tread Size:1.375 inchesMaterial:Aluminum alloyAluminum alloySurface Treatment:NickelStraight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aDint Of Measure:Pemilitarization:NoFig:	Thready Qty Per Inch (tpi):	
1.375 inches Material: Material: Aluminum alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Linef Fig: No	18	
Material:Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefSheff Life:N/aDint of Measure:-Demiltarization:NoFig:	Thread Size:	
Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aDint of Measure:-NoFing:Fing:	1.375 inches	
Surface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aDint Of Measure:Demilitarization:NoFig:	Material:	
Nickel Style Designator: Straight type w/cable clamp Surface Treatment: Nickel Nickel Thread Series Designator: Unef Shelf Life: N/a Life: N/a Life: Int Of Measure: Inter Series	Aluminum alloy	
Style Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Surface Treatment:	
Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Nickel	
Surface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Style Designator:	
Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Straight type w/cable clamp	
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nickel	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Unef	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A10100	Fiig:	
	A10100	