

View Online at <https://aerobasegroup.com/nsn/5935-01-143-3677>

**Body Style:**

Right angle type

**Overall Length:**

5.650 inches

**Overall Height:**

0.250 inches

**Overall Width:**

0.450 inches

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

5.400 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end 1st contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Side single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

**Terminal Type:**

Solder well single mating end 1st contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end 1st contact grouping

**Guide Design And Location:**

D shape socket right-hand at 6 o'clock

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

45 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.045 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.