

View Online at <https://aerobasegroup.com/nsn/5935-01-143-5072>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

4.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.808 inches

Overall Height:

1.075 inches

Overall Width:

0.902 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

244 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Post jacksocket

Thready Qty Per Inch (tpi):

32

Thread Size:

0.312 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade b or c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gbt-30f military specification single material response single mating end

Included Contact Quantity:

244 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.244 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28804/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.