NSN 5935-01-144-1155

Contact Surface Treatment:

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-144-1155



Thread Class: 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.510 inches **Overall Height:** 1.022 inches **Overall Width:** 4.325 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.875 inches **Distance From Mounting Shoulder To Front Face:** Between 0.519 inches and 0.539 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Err-090 single mating end **Contact Removability:** Removable single mating end 1st contact grouping **Polarization Method:** Mating end **Shell Type:** Solid **Connector Locking Method:** Spring lock Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

NSN 5935-01-144-1155

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end 1st contact grouping
Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, cl 1 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
52 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Special Features:
Contact designator 59c7p
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26074 spec