

View Online at <https://aerobasegroup.com/nsn/5935-01-144-1156>

Body Style:

Straight edge type w/mounting flange

Overall Length:

152.8 millimeters

Overall Width:

6.0 millimeters

Environmental Protection:

Corrosion resistant

Distance Between Mounting Facility Centers:

145.8 millimeters

Board Accommodated Length:

127.6 millimeters single board

Board Accommodated Width:

Between 1.5 millimeters and 1.8 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

230.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

330.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polysulfone single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.