NSN 5935-01-144-6475

Thread Class:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-144-6475

specification 2nd treatment response single mating end single contact grouping

Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
1.655 inches
Overall Height:
0.462 inches
Environmental Protection:
Cold resistant and heat resistant
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 2 federal

NSN 5935-01-144-6475

Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Pin single mating end single contact grouping Contact Material Specification: Qq-b-626 federal specification single material

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833 ty gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.