

View Online at https://aerobasegroup.com/nsn/5935-01-144-6616

| Thread Class: | |
|---|---|
| 2b | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape, rectangular | |
| Overall Length: | |
| 1.675 inches | |
| Overall Height: | |
| 1.130 inches | |
| Overall Width: | |
| 2.830 inches | |
| Environmental Protection: | |
| Corrosion resistant and shock resistant and vibration resist | stant |
| Center To Center Distance Between Mounting Facilitie | es Parallel To Height: |
| 0.812 inches | |
| Distance Between Centerlines Of Mounting Facilities | Parallel To Body Width: |
| 2.500 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 104 single mating end | |
| Polarization Method: | |
| Guide pin/socket | |
| Connector Locking Method: | |
| Jackscrew | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Thread Size: | |
| 0.138 inches | |
| Insert Material: | |
| Plastic diallyl phthalate single mating end | |
| Insert Material Specification: | |
| Mil-p-19833, ty gdi-30f military specification single materia | al response single mating end or mil-m-14, ty sdg military specification single |
| material response single mating end | |
| Unable To Decode: | |
| Unable to decode and unable to decode and unable to de | ecode and unable to decode |
| Thread Series Designator: | |
| Unc | |

Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.