

View Online at <https://aerobasegroup.com/nsn/5935-01-144-7685>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Rectangular shape, w/jackscrew

**Overall Length:**

Between 2.865 inches and 2.885 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 2.490 inches and 2.510 inches

**Overall Height:**

5.100 inches

**Overall Width:**

Between 1.850 inches and 1.870 inches

**Environmental Protection:**

Thermal shock resistant and humidity resistant and corrosion resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.149 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.240 inches and 1.260 inches

**Threaded Device Type:**

Coupling facility and coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

158 single mating end

**Polarization Method:**

Polarization boss and guide pin/socket

**Connector Locking Method:**

Jackscrew

**Operating Temperature Rating:**

Between -54.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

28 and 24

**Thread Size:**

0.250 inches

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

**Thread Series Designator:**

Unf and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.