

View Online at <https://aerobasegroup.com/nsn/5935-01-144-7685>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Rectangular shape, w/jackscrew

Overall Length:

Between 2.865 inches and 2.885 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.490 inches and 2.510 inches

Overall Height:

5.100 inches

Overall Width:

Between 1.850 inches and 1.870 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and corrosion resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.149 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.240 inches and 1.260 inches

Threaded Device Type:

Coupling facility and coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

158 single mating end

Polarization Method:

Polarization boss and guide pin/socket

Connector Locking Method:

Jackscrew

Operating Temperature Rating:

Between -54.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

28 and 24

Thread Size:

0.250 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Thread Series Designator:

Unf and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.