## NSN 5935-01-145-3046

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-145-3046 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Height:** 1.312 inches **Overall Diameter:** 0.750 inches **Environmental Protection:** Watertight and vibration resistant and corrosion resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 115.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction Thread Length: 0.500 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

## NSN 5935-01-145-3046

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
2 single mating end single contact grouping
<b>Bushing Accommodation Hole Shape:</b>
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.002 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0