Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-145-4610

Body Style:

Straight type

Overall Length:

1.536 inches

Overall Width:

0.420 inches

Body Height:

0.483 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

End Application:

5b-1 aircraft support equipment. Spruance class dd (963), tarawa class lha, forrestal class cv, nimitz class cvn, arleigh burke class ddg, los angeles class ssn (688), ticonderoga class cg (47). Mx peacekeeper missle support equipment. An/msr-t4.

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0