Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-145-6194

## Thread Class:

2a

**Thread Direction:** 

Right-hand

### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

1.532 inches

**Overall Height:** 

1.500 inches

**Overall Width:** 

1.500 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

#### Unthreaded Mounting Hole Diameter:

0.120 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

### Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.760 inches

#### **Threaded Device Type:**

Coupling facility

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

20-11 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

### **Polarization Method:**

Key, multiple key groove

# **Insert Position In Deg:**

0.0

#### Shell Type:

Solid



**Connector Locking Method:** 

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.250 inches

Terminal Location: Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Rubber synthetic single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

**Included Contact Quantity:** 

13 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

 $0.013 \ \text{gold} \ \text{grains}, \ \text{troy} \ \text{and} \ 0.013 \ \text{silver} \ \text{grains}, \ \text{troy}$ 

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0