NSN 5935-01-145-7224

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-145-7224

Body Style:
Straight shape
Overall Length:
4.000 inches
Overall Height:
1.290 inches
Overall Width:
0.300 inches
Body Length:
3.260 inches
Unthreaded Mounting Hole Diameter:
0.100 inches
Distance Between Mounting Facility Centers:
3.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Latch
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2
federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

NSN 5935-01-145-7224

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Square pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.