Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-145-9862

| Overall Length: | |
|---------------------|--|
| 1.664 inches | |
| Overall Height: | |
| 1.375 inches | |
| Overall Width: | |
| 1.375 inches | |
| Environmental Pro | tection: |
| Weather resistant | |
| Unthreaded Moun | ing Hole Diameter: |
| 0.150 inches | |
| Center To Center | Distance Between Mounting Facilities Parallel To Height: |
| 1.062 inches | |
| Distance Between | Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.062 inches | |
| Distance From Mo | unting Shoulder To Front Face: |
| 0.797 inches | |
| Mating End Quant | ty: |
| 1 | |
| Contact Removable | lity: |
| Removable single r | nating end single contact grouping |
| Polarization Metho | d: |
| Keyway or multiple | keyway |
| Shell Type: | |
| Solid | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Trea | tment: |
| Oxide | |
| Included Contact (| Quantity: |
| 10 single mating en | d single contact grouping |
| Included Contact | |
| Round pin single m | ating end single contact grouping |
| Test Data Docume | |
| 81349-mil-c-22999 | specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| | mmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| | performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| | |



Mil-std (military Standard):

Mil-c-22992 spec.