

View Online at <https://aerobasegroup.com/nsn/5935-01-146-1972>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.125 inches

**Overall Height:**

3.000 inches

**Overall Width:**

3.000 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and waterproof

**Unthreaded Mounting Hole Diameter:**

0.173 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.375 inches

**Distance From Mounting Shoulder To Front Face:**

0.875 inches

**Threaded Device Type:**

Back shell and coupling facility and hub

**Mating End Quantity:**

1

**Polarization Method:**

Keyway or multiple keyway and polarization boss

**Insert Position In Deg:**

72.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.467 inches and 0.625 inches

**Thready Qty Per Inch (tpi):**

16 and 16

**Thread Size:**

2.750 inches and 2.750 inches

**Insert Material:**

Rubber single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and passivate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un and un

**Specification Data:**

96906-ms3400 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.