NSN 5935-01-146-9079

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-146-9079

Body Style:

Straight shape w/flange

Bushing Diameter:

1.625 inches

Overall Diameter:

2.500 inches

Environmental Protection:

Heat resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance From Mounting Shoulder To Rear Face:

1.907 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

130-2-iec-18 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/142 government specification

Shelf Life:

N/a

NSN 5935-01-146-9079

Electrical Receptacle Connector - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A039b0