Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-146-9079

| Body Style:   |
|---|
| Straight shape w/flange   |
| Bushing Diameter:   |
| 1.625 inches  |
| Overall Diameter:   |
| 2.500 inches  |
| Environmental Protection:   |
| Heat resistant and salt water resistant                               |
| Unthreaded Mounting Hole Diameter:                                    |
| 0.156 inches  |
| Distance From Mounting Shoulder To Rear Face:                         |
| 1.907 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                                   |
| 130-2-iec-18 single mating end  |
| Contact Removability:   |
| Removable single mating end all contact groupings                     |
| Contact Maximum Current Rating In Amps:                               |
| 20.0 single mating end all contact groupings                          |
| Contact Maximum Ac Voltage Rating In Volts:                           |
| 125.0 single mating end all contact groupings                         |
| Polarization Method:  |
| Contact   |
| Shell Type:   |
| Solid   |
| Terminal Location:  |
| Back single mating end all contact groupings                          |
| Contact Material:   |
| Copper alloy single mating end all contact groupings                  |
| Terminal Type:  |
| Screw single mating end all contact groupings                         |
| Included Contact Quantity:  |
| 2 single mating end 2nd contact grouping                              |
| Included Contact Type:  |
| Round socket single mating end 1st contact grouping                   |
| Test Data Document:   |
| 81348-w-c-596 specification (includes engineering type bulletins, bro |

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81348-w-c-596/142 government specification

Shelf Life:

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0