Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-146-9087

### **Thread Class:**

2a and 2b

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape

# **Overall Length:**

2.350 inches

#### **Overall Height:**

0.485 inches

Overall Width:

0.250 inches

## **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

#### Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

## **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

## Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end

# NSN 5935-01-146-9087

Electrical Plug Connector - Page 2 of 2



# **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.