

View Online at <https://aerobasegroup.com/nsn/5935-01-147-2525>

**Environmental Protection:**

Pressure proof and watertight

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Afea 5 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1872.0 all mating ends single contact grouping

**Polarization Method:**

Key, multiple key groove

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Steel single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-c-2421 (ships) military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Included Contact Quantity:**

5 single mating end single contact grouping

**Special Features:**

Operable in submarine applications to 10000 psig hydrostatic pressure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-24217 spec.