## NSN 5935-01-147-5763

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-147-5763

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

5.135 inches

**Overall Height:** 

0.988 inches

**Overall Width:** 

0.368 inches

**Environmental Protection:** 

Humidity resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

**4.875** inches

**Board Accommodated Length:** 

4.400 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.078 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Polarization Method:** 

Inter-contact polarizing keys

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping and tin single mating end single contact grouping

**Insert Material:** 

Plastic polyester single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:** 

43 single mating end single contact grouping

## NSN 5935-01-147-5763

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type
-----------------------

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.043 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0