

View Online at <https://aerobasegroup.com/nsn/5935-01-147-5763>

Body Style:

Straight edge type w/mounting flange

Overall Length:

5.135 inches

Overall Height:

0.988 inches

Overall Width:

0.368 inches

Environmental Protection:

Humidity resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

4.875 inches

Board Accommodated Length:

4.400 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.078 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and tin single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

43 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.043 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0