Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-147-8946

# Thread Class:

2a and 2b and 2a

## **Thread Direction:**

Right-hand and right-hand and right-hand

## **Body Style:**

Straight shape

## **Overall Length:**

1.480 inches

#### **Overall Height:**

0.570 inches

**Overall Width:** 

#### 0.390 inches

## **Distance Between Mounting Facility Centers:**

1.267 inches

#### **Threaded Device Type:**

Coupling facility and mounting stud

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

44 single mating end

## Contact Removability:

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

## **Connector Locking Method:**

Jackscrew-socket

## Thready Qty Per Inch (tpi):

48 and 48 and 56

## Thread Size:

0.099 inches and 0.099 inches and 0.086 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping

# NSN 5935-01-147-8946

Electrical Receptacle Connector - Page 2 of 2



**Insert Material Specification:** Mil-m-14, sdg-f military specification single material response single mating end **Included Contact Quantity:** 44 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.044 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.