Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-148-3274

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
4.297 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.871 inches
Overall Width:
Between 1.146 inches and 1.170 inches
Environmental Protection:
Moisture resistant and shock resistant and corrosion resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
Between 0.195 inches and 0.200 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.558 inches and 0.566 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Thready Qty Per Inch (tpi):
24
Thread Size:
0.190 inches
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping
Insert Material:
Plastic single mating end

NSN 5935-01-148-3274

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping **Terminal Type:** Wire wrap single mating end 1st contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end 1st contact grouping Shell Material: Aluminum alloy 380.0 **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074 cl 1 military specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 52 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end 1st contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.052 gold grains, troy and 0.052 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.
