NSN 5935-01-148-3275

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-148-3275 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 4.297 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.871 inches **Overall Height:** 2.620 inches **Overall Width:** Between 1.146 inches and 1.170 inches **Environmental Protection:** Moisture resistant and shock resistant and corrosion resistant and thermal shock resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.558 inches and 0.566 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end 1st contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid Thready Qty Per Inch (tpi): **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping **Contact Surface Treatment:** Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping

Insert Material:

Plastic single mating end

NSN 5935-01-148-3275

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-q-45204 military specification 1st treatment response single mating end 1st contact grouping

Terminal Type:

Wire wrap single mating end 1st contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end 1st contact grouping

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 cl 1 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

52 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.052 gold grains, troy and 0.052 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.