NSN 5935-01-148-3276

Thread Class:

Thread Direction:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-148-3276

Right-hand
Body Style:
Straight shape
Overall Length:
4.297 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.871 inches
Overall Width:
Between 1.146 inches and 1.170 inches
Environmental Protection:
Moisture resistant and shock resistant and corrosion resistant and thermal shock resistant
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.558 inches and 0.566 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping

NSN 5935-01-148-3276

Electrical Receptacle Connector - Page 2 of 2



grouping

Terminal Type:
Wire wrap single mating end 1st contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end 1st contact
Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 cl 1 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
52 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.052 gold grains, troy and 0.052 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Ū

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.