Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-148-5408

#### **Body Style:**

Angle shape, external coupling

#### **Overall Length:**

0.594 inches

# **Bushing Diameter:**

0.062 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

#### 0.312 inches

#### **Overall Height:**

0.875 inches

#### **Overall Width:**

#### 0.438 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

#### 0.312 inches

**Distance From Mounting Shoulder To Rear Face:** 

#### 0.375 inches

Flange Length:

0.438 inches

- Mating End Quantity:
- 1
- **Contact Position Arrangement Style:**

Nonstd single mating end

# Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

#### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Silver single mating end single contact grouping

# **Insert Material:**

Plastic tetrafluoroethylene single mating end

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver



**Included Contact Quantity:** 

1 single mating end single contact grouping

# **Precious Material And Location:**

Contact surface silver and shell surface silver

**Precious Material:** 

Silver

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0