
Electrical Plug Connector - Page 1 of 2





## Thread Class:

2b

Thread Direction:

Right-hand

## **Body Style:**

Angle shape w/cable clamp

## **Overall Diameter:**

0.946 inches

#### **Body Angle In Deg:**

90.0

#### Cable Entrance Diameter:

0.312 inches

#### **Threaded Device Type:**

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

10sl-3 single mating end

## **Contact Removability:**

Nonremovable single mating end all contact groupings

## **Polarization Method:**

Keyway or multiple keyway

## Insert Position In Deg:

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Internally threaded coupling nut

## **Connector Cable Strain Relief Method:**

Cable clamp

## **Distance From Centerline To Connector End:**

1.487 inches

## **Distance From Centerline To Cable End:**

1.769 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.625 inches

## **Terminal Location:**

Side single mating end all contact groupings

## **Contact Material:**

Nickel alloy single mating end 2nd contact grouping

# NSN 5935-01-148-6679

Electrical Plug Connector - Page 2 of 2



**Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy Shell Surface Treatment: Anodize **Included Contact Quantity:** 1 single mating end 3rd contact grouping Included Contact Type: Round socket single mating end all contact groupings **Special Features:** Contact configuration is 10sl-55 **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0