## NSN 5935-01-148-7767

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-148-7767 **Overall Length:** 0.524 inches **Overall Height:** 1.141 inches Overall Width: **1.141** inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.462 inches **Mating End Quantity: Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Insert Material:** Rubber single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074, cl 3, grade b military specification single treatment response **Test Data Document:** 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 96906-ms3115 government standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5935-01-148-7767

Receptacle Dummy Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.