

View Online at <https://aerobasegroup.com/nsn/5935-01-148-7783>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.187 inches

**Overall Height:**

0.680 inches

**Overall Width:**

0.348 inches

**Environmental Protection:**

Cold resistant and heat resistant

**Distance Between Mounting Facility Centers:**

2.937 inches

**Board Accommodated Length:**

2.624 inches single board

**Board Accommodated Width:**

0.062 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1800.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

15 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.