

View Online at <https://aerobasegroup.com/nsn/5935-01-148-8462>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Hood, side opening w/clamp

**Overall Length:**

2.656 inches

**Overall Height:**

2.269 inches

**Overall Width:**

1.130 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Cable Entrance Diameter:**

0.340 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

50 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Hood, side opening

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Length:**

0.320 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Metal single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 1, grade c military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 type 2, cl 1 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 ty sdg-f military specification single material response single mating end

**Shell Guide Type And Location Designator:**

C slot

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-28748/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

1-0001-0

**Mil-std (military Standard):**

Mil-g-45204 spec.