## NSN 5935-01-149-2520

**Unthreaded Mounting Hole Diameter:** 

Round pin single mating end single contact grouping

Body Style:
Straight type
Overall Length:
3.350 inches
Overall Height:
0.715 inches
Overall Width:
0.250 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-149-2520

0.120 inches
Distance Between Mounting Facility Centers:
3.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Guide Design And Location:
D shape pin left-hand at 6 oclock and d shape socket right-hand at 6 oclock
Insert Material Specification:
Mil-m-24519 military specification single material response single mating end
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:

## NSN 5935-01-149-2520

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.