## NSN 5935-01-149-2995

**Thread Class:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-149-2995

2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.047 inches
Environmental Protection:
Cold resistant and heat resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Smc single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded shell
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2, grade c military specification single treatment response single mating end single contact grouping

## NSN 5935-01-149-2995

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204 military specification single treatment response
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.101 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.