Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-149-6970



# **Thread Class:** 2a **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling **Overall Length:** 1.234 inches **Overall Diameter:** 1.156 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell Mating End Quantity: 1 **Contact Position Arrangement Style:** 13-8 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 328.0 Shell Type: Solid **Connector Locking Method: Bayonet latch Thread Length:** 0.219 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

# NSN 5935-01-149-6970

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

### **Included Contact Quantity:**

8 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.008 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef

Specification Data: 96906-ms27467 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A039b0

# Mil-std (military Standard):

Mil-c-38999 spec.