## NSN 5935-01-149-8514

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-149-8514 **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.125 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Unthreaded Mounting Hole Diameter:** Between 0.172 inches and 0.187 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.843 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 250.0 Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Stainless steel

**Shell Surface Treatment:**Passivate

## NSN 5935-01-149-8514

Electrical Receptacle Connector - Page 2 of 2



| Inclu | uded | Contact | Quantity | <b>/</b> : |
|-------|------|---------|----------|------------|
|       |      |         |          |            |

37 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.