

View Online at <https://aerobasegroup.com/nsn/5935-01-149-9381>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.782 inches

Overall Height:

1.234 inches

Overall Width:

1.234 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.970 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.970 inches

Distance From Mounting Shoulder To Front Face:

Between 0.317 inches and 0.322 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

16-99 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Thready Qty Per Inch (tpi):

20

Thread Size:

0.938 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

21 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27472 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-45204