

View Online at <https://aerobasegroup.com/nsn/5935-01-149-9383>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.232 inches

Overall Height:

1.141 inches

Overall Width:

1.141 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Distance From Mounting Shoulder To Front Face:

Between 0.462 inches and 0.493 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

40455 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

24

Thread Size:

0.562 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 3 federal specification 1st treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.