AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-150-1722

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.327 inches and 1.347 inches
Overall Height:
Between 1.695 inches and 1.711 inches
Overall Width:
Between 1.695 inches and 1.711 inches
Environmental Protection:
Moisture proof and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.130 inches and 0.160 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.370 inches and 1.380 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.370 inches and 1.380 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
24-155 single mating end
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
50.0 and 160.0 and 190.0 and 225.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
1.500 inches
Shell Material:
Aluminum alloy 6061

## NSN 5935-01-150-1722

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 cl iii, grade a military specification single treatment response

Shell Material Specification:

Qq-a-367 t-6 federal specification single material response

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Un

Specification Data: 81349-mil-c-81511/41 government specification Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-c-26074 spec.