

View Online at <https://aerobasegroup.com/nsn/5935-01-150-3317>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

0.925 inches

**Overall Diameter:**

0.500 inches

**Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant and moisture resistant

**Distance From Mounting Shoulder To Front Face:**

0.350 inches

**Mounting Facility Thickness:**

0.250 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Osm all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded coupling nut and friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

36 and 36

**Thread Size:**

0.250 inches and 0.250 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Gold

**Shell Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response

**Insert Material Specification:**

Mil-p-19468 military specification 1st material response all mating ends and I-p-403 federal specification 2nd material response all mating ends

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/double flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.