NSN 5935-01-150-6391

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-150-6391 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.461 inches and 1.651 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Unthreaded Mounting Hole Diameter:** Between 0.171 inches and 0.177 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** Between 0.875 inches and 0.885 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 36-1 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 23.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-01-150-6391

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
16
Thread Size:
2.250 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
4 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.022 gold grains, troy and 0.022 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0