NSN 5935-01-151-1237

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-151-1237 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.452 inches **Body Angle In Deg:** 90.0 **Environmental Protection:** Salt water resistant and shock proof and vibration proof **Cable Entrance Diameter:** 0.740 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 850.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End:** 2.035 inches **Distance From Centerline To Cable End:**

1.884 inches

NSN 5935-01-151-1237Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.055 gold grains, troy and 0.055 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0