NSN 5935-01-151-1256

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-151-1256 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-17 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 13.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 3rd contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 80.0

Shell Type:

Solid

NSN 5935-01-151-1256

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
3 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.015 gold grains, troy and 0.015 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0