NSN 5935-01-151-9261

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-151-9261

Body Style:
Angle shape w/cable clamp
Overall Diameter:
1.800 inches
Body Angle In Deg:
90.0
Cable Entrance Diameter:
0.656 inches
Mating End Quantity:
Contact Position Arrangement Style:
24-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
270.0
Shell Type:
Solid
Connector Locking Method:
Payonat latab
Bayonet latch
Connector Cable Strain Relief Method:
·
Connector Cable Strain Relief Method:
Connector Cable Strain Relief Method: Cable clamp
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End:
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location:
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Terminal Type:
Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Cable End: 1.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping

Cadmium and chromate

NSN 5935-01-151-9261

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.061 gold grains, troy and 0.061 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0