

View Online at <https://aerobasegroup.com/nsn/5935-01-152-4779>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.125 inches

Overall Diameter:

Between 2.812 inches and 2.822 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

Between 0.961 inches and 0.971 inches

Mounting Facility Thickness:

0.128 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

36-10 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

16 and 16 and 16

Thread Size:

2.250 inches and 2.250 inches and 2.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

48 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.048 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un and un and un

Specification Data:

96906-ms3404 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0