Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-152-6806

| Body Style:   |
|---|
| Straight type   |
| Overall Length:   |
| 2.300 inches  |
| Overall Height:   |
| 0.650 inches  |
| Overall Width:  |
| 0.300 inches  |
| Environmental Protection:   |
| Cold resistant and heat resistant   |
| Distance Between Mounting Facility Centers:   |
| 2.000 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 2 rows of contacts non-inserted board single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 1.0 single mating end single contact grouping   |
| Contact Maximum Dc Voltage Rating In Volts:   |
| 500.0 single mating end single contact grouping   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material:  |
| Plastic single mating end   |
| Included Contact Quantity:  |
| 26 single mating end single contact grouping  |
| Included Contact Type:  |
| Flat pin single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.026 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Shelf Life:   |
| N/a   |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0