## NSN 5935-01-152-6876

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-152-6876 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.781 inches **Overall Height:** 3.000 inches **Overall Width:** 3.000 inches **Unthreaded Mounting Hole Diameter:** 0.173 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.375 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 44-52 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 70.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-01-152-6876

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
16
Thread Size:
2.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.104 gold grains, troy and 0.104 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0