

View Online at <https://aerobasegroup.com/nsn/5935-01-152-8974>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, rectangular

**Overall Width:**

1.141 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

1.312 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

26 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Shell and jackscrew

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

32 and 32 and 40

**Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 type 2, cl 1 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 ty sgd-f military specification single material response single mating end

**Shell Guide Type And Location Designator:**

E slot

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

26 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Jackscrew type-female and location-left hand and jackscrew type-male and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc and unc and unc

**Specification Data:**

81349-mil-c-28748/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.